FLOOR TREATMENT



High-shine and resistant self-shining acrylic emulsion

Pictograms of use:





Packaging:

TSTM005: 4 l. Container – 4 units
TSTM006: 10 l. Container – 1 unit

Signage Pictograms:

GENERAL HEALTH REGISTER FOR FOODS: **37-00000271/M**

Company certified by BVQI:
Nº ESPMDD006325/ISO 14001
ENVIRONMENTAL MANAGEMENT

Description:

Self-shine emulsion, made of acrylic polymers and first class waxes, for marble and terrazzo floors, rubber, linoleum and plastic pavements.

Key Properties :

Especially developed for hard floors, where a high durability and resistance to traffic is desired. Maximum brightness and protection level for the treated surface. Suitable for its maintenance with mop or high speed rotating machine.

Use Instructions:

Make a first cleaning of the surface to be treated with the THOMIL FLOOR STRIPPER, to remove dirtiness and any other wax rests. Dry.
Apply PLUS-2 WAX directly on the floor and spread a thin and uniform layer, with a polisher or mop.
Let dry for at least 30 minutes (depending on humidity, porosity ...).
Apply a second layer perpendicular to the first one.
On especially porous floors, a prior sealing with THOMIL SEALANT is recommended.
Maintenance of the film can be made with the high speed Spray-Cleaner method, with H.S. PLUS.

Technical Data:

* PROPERTIES: Metal glaze wax. Self-shining and anti-slipping. Direct use. High brightness and resistance, suitable for maintenance with mop or medium and high speed rotating machine. Short drying period.
* SPECIFICATIONS:
Appearance: Light liquid
Colour: white
Odour: Characteristic
Density (20º): 1.045 +/- 0.005 Gc/cc
PH (20º): 9 +/- 0.5
Dry Residue: 24.5 +/- 0.5%
* COMPOSITION: Polymères acryliques. Acrylic polymers. Waxes, plasticizer, moisturizers, resins and additives.

Preservation and Storage:

Keep in its original package tightly closed, protecting it from cold and intense heat. Avoid freezing. Do not expose to direct sunlight.

Security and Handling:

Safety data sheet available on request. FOR PROFESSIONAL USE.

Warnings:

In case of accidental ingestion, please contact the National Toxicology Service.

Our TECHNICAL DEPARTMENT will attend any doubts or questions you have about products or applications without obligation.
Tel. (+34) 91 6910263

NOTE: The warranty of Thomil applies only to the quality of the product, and does not assume liability for improper use of it.

Ctra. Andalucía, km. 18, 28320 Pinto (Madrid) www.thomil.com: profesional@thomil.com